

Technical Data Sheet

AF-205

Ingredient	Silicone oil
Warranty	12 months (kept in a cool, dry place at room
	temperature)
Applications	AF-205 is used in
	 Defoaming of non-aqueous systems
	 Defoaming in the petroleum industry
Features	• Excellent defoaming and foam suppression
	properties at low usage levels
	• Easy to disperse in solvent

Physical indicators

Exterior Colorless or light yellow liquid

Viscosity, 25°C 1-200mPa.s

Instructions

- It can be added directly to the non-aqueous phase system, the recommended addition amount is 100~1000ppm.
- It is recommended to use volumetric pump metering to optimize dosing during continuous or semi-continuous operation.



Precautions	There are no fatal or harmful ingredients to
	the human body, but try not to touch it
	directly or use it if it accidentally gets into
	the eyes, rinse with clean water
	• Storage at room temperature (5-40 $^{\circ}$ C), away
	from direct sunlight
	• Refer to the product's Material Safety Data
	Sheet (MSDS) before use
Usage	 Not for human injection
restrictions	• This product is not tested or represented as
	suitable for medical or pharmaceutical use
Package	• 25kg/50kg plastic drum/1000kg IBC drum

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.