

Technical Data Sheet

AF-406

Ingredient	Hydroxy compound aqueous emulsion
Warranty	6 months (kept in a cool, dry place at room
	temperature)
Applications	AF-406 is used in the wet end of papermaking
	 Production technology of boxboard paper,
	white board paper and corrugated paper
	 Production technology of newsprint,
	carbonless copy paper, and cultural paper
	 Suitable for production processes using dry
	strength agents and sizing agents
	 Suitable for neutral and acid sizing processes
Features	• The product itself has low viscosity and is
	suitable for pumping and adding.
	 Does not affect the function of other
	papermaking chemicals, such as sizing
	agents and retention aids
	 Does not contain silicone oil components
	that can cause paper defects



Suitable for white water temperature
 20~50°C, excellent degassing performance
 and anti-foaming performance

Physical indicators

Exterior White or slightly yellow milky liquid

Solid content (28-30) %

pH value 6.0-8.0

Instructions

- Add directly for use, or dilute online for use
- Consumption per ton of paper 100~500g
- The optimal addition amount is determined according to the actual situation on site
- The adding point is usually the white water pool under the net or the white water tank outside the machine.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away
 from direct sunlight



	• Refer to the product's Material Safety Data
	Sheet (MSDS) before use
Usage	 Not for human injection
restrictions	• This product is not tested or represented as
	suitable for medical or pharmaceutical use
Package	• 200kg plastic drum or 1000kg IBC drum

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.