

Viscosity, 25℃

Instructions

Technical Data Sheet

AF-822

Ingredient	Silicone oil and hydrophobic particles of water
	emulsion
Warranty	6 months (kept in a cool, dry place at room
	temperature)
Applications	AF-822 is used in
	 Textile printing and dyeing
	Oil drilling
	 Industrial cleaning
Features	 Fast defoaming and lasting defoaming
	 Good stability and acid and alkali resistance
Physical indicators	
Exterior	White or yellowish milky liquid
Solid conte	nt (24-26) %
pH value	6.0-9.0

5000-15000mPa.s

content.

• It can be used directly or diluted to a low



- It can be diluted directly with water, but need to be used immediately, if the dilution needs to be stored for a certain time, you can consult our company, our company will provide professional dilution method.
- The addition amount is generally 10~1000ppm, and the optimal addition amount is determined according to the actual situation on site.
- The addition point is generally selected where the defoamer is easily dispersed, and can be continuously added with a metering pump.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away
 from direct sunlight
- Refer to the product's Material Safety Data
 Sheet (MSDS) before use

Usage

Not for human injection



restrictions	• This product is not tested or represented as	
	suitable for medical or pharmaceutical use	
Package	• 25kg/200kg plastic drum or 1000kg IBC	
	drum	

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.