

Technical Data Sheet

AF-713

Ingredient	Hydroxy compounds
Warranty	12 months (kept in a cool, dry place at room
	temperature)
Applications	AF-713 is used in fermentation, sewage
	treatment, desulfurization.
	 Fermentation production process
	• Industrial wastewater treatment, landfill
	leachate, industrial circulating water
	Power plant desulfurization
Features	The product has outstanding anti-foaming
	ability
	 Better acid and alkali resistance
	 The product disperses easily in water
	• High temperature resistance, can withstand
	temperatures above 100°C

Physical indicators

Exterior Colorless or light yellow liquid

pH value 5.0-8.0

Viscosity, 25°C 200-800mPa.s



Instructions

- It can be added directly and is not recommended for dilution.
- The addition amount is generally 100~1000ppm. The optimal addition amount is determined according to the actual situation on site.
- The adding point is generally a place where the foam is rich and the defoaming agent is easily dispersed.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away
 from direct sunlight
- Refer to the product's Material Safety Data Sheet (MSDS) before use

Usage

• Not for human injection

restrictions

• This product is not tested or represented as suitable for medical or pharmaceutical use

Package

25kg/200kg plastic drum or 1000kg IBC drum





LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.