

Technical Data Sheet

AF-801

Ingredient Hydroxy compound

Warranty 12 months (kept in a cool, dry place at room temperature)

Applications AF-801 is used in

- Garbage leachate
- Polycarboxylic acid water reducer
- Calcium silicate board

Features

- Easy to disperse
- Long-lasting foam suppression
- Good compatibility with polycarboxylic acid superplasticizer
- Does not contain silicone, will not have a negative impact on the system

Physical indicators

Exterior Colorless or yellow transparent liquid

pH value 6.0-9.0

Instructions ● Use it directly. Do not dilute it.

-
- The addition amount is 0.1~1.0%.
 - The optimal addition amount is determined according to the actual situation on site.
 - The addition point is generally the part where the foam is rich and the defoamer is easily dispersed.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away from direct sunlight
- Refer to the product's Material Safety Data Sheet (MSDS) before use

Usage

- Not for human injection

restrictions

- This product is not tested or represented as suitable for medical or pharmaceutical use

Package

- 25kg/200kg plastic drum or 1000kg IBC drum

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights