

## **Technical Data Sheet**

## AF-192

Ingredient	Hydroxy compound aqueous emulsion
Warranty	6 months (kept in a cool, dry place at room
	temperature)
Applications	AF-192 is used in
	• Sewage treatment
	• Textile auxiliaries
	• Cement mortar
Features	• Fast defoaming
	• Easily dispersed in the use system
	• Good compatibility with the system used
Physical indic	ators
Exterior	White solid powder or granules
pH value	4.0-8.0
Instructions	• Add directly for use, not suitable for dilution
	• Adding amount 0.1%~0.6%
	• The optimal addition amount is determined
	according to the actual situation on site



Precautions	• There are no fatal or harmful ingredients to
	the human body, but try not to touch it
	directly or use it if it accidentally gets into
	the eyes, rinse with clean water
	• Storage at room temperature (5-40 $^{\circ}$ C), away
	from direct sunlight
	• Refer to the product's Material Safety Data
	Sheet (MSDS) before use
Usage	• Not for human injection
restrictions	• This product is not tested or represented as
	suitable for medical or pharmaceutical use
Package	• 25 kg bag

## LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.