

Technical Data Sheet

AF-601

Ingredient	Fatty acid esters
Warranty	12 months (kept in a cool, dry place at room
	temperature)
Applications	AF-601 is used in papermaking wet-end.
	 Production technology of cardboard,
	corrugated paper and other paper types
	 Suitable for production processes using dry
	strength agents and sizing agents
Features	• The product has low viscosity and is suitable
	for pumping addition
	● Applicable white water temperature 45~60°C
	 Good degassing performance
	• The product disperses easily in water

Physical indicators

Exterior Yellow or brown liquid

Solid content 100%

pH value 6.0-9.0

Viscosity, 25℃ <1000mPa.s



Instructions

- It can be added directly and is not recommended for dilution.
- Paper consumption per ton 100~500g. The optimal addition amount is determined according to the actual situation on site.
- The adding point for the papermaking wet-end is usually the white water pool under the net or the white water tank outside the machine.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away
 from direct sunlight
- Refer to the product's Material Safety Data
 Sheet (MSDS) before use

Usage

• Not for human injection

restrictions

• This product is not tested or represented as suitable for medical or pharmaceutical use

Package

25kg/200kg plastic drum or 1000kg IBC drum





LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.