

Technical Data Sheet

AF-733

Ingredient	Mineral oil and hydrophobic particles
Warranty	6 months (kept in a cool, dry place at room
	temperature)
Applications	AF-733 is used in
	• Water-based ink
Features	• Fast defoaming and long-lasting defoaming
	• Good dispersion and compatibility in the
	system
Physical indic	ators
Exterior	Milky white to light yellow oily liquid
pH value	5.0-7.0
Viscosity, 2	5°C 400-1200mPa.s
Instructions	• Add ink after mixing.
	• The addition amount is generally 0.05~0.5%,
	and the optimal addition amount is adjusted
	according to the actual situation on site.
Precautions	• There are no fatal or harmful ingredients to
	the human body, but try not to touch it

	directly or use it if it accidentally gets into
	the eyes, rinse with clean water
	• Storage at room temperature (5-40 $^{\circ}$ C), away
	from direct sunlight
	• Refer to the product's Material Safety Data
	Sheet (MSDS) before use
Usage	• Not for human injection
restrictions	• This product is not tested or represented as
	suitable for medical or pharmaceutical use
Package	• 25kg/50kg/180kg plastic drum or 850kg IBC
	drum

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.