

Technical Data Sheet

AF-801

Instructions

Ingredient	Hydroxy compound
Warranty	12 months (kept in a cool, dry place at room
	temperature)
Applications	AF-801 is used in
	Garbage leachate
	Polycarboxylic acid water reducer
	Calcium silicate board
Features	Easy to disperse
	 Long-lasting foam suppression
	 Good compatibility with polycarboxylic acid
	superplasticizer
	 Does not contain silicone, will not have a
	negative impact on the system
Physical indicators	
Exterior	Colorless or yellow transparent liquid
pH value	6.0-9.0

• Use it directly. Do not dilute it.

The addition amount is $0.1\sim1.0\%$.

1



- The optimal addition amount is determined according to the actual situation on site.
- The addition point is generally the part where the foam is rich and the defoamer is easily dispersed.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away
 from direct sunlight
- Refer to the product's Material Safety Data
 Sheet (MSDS) before use

Usage

Not for human injection

restrictions

 This product is not tested or represented as suitable for medical or pharmaceutical use

Package

 25kg/200kg plastic drum or 1000kg IBC drum

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights