

Technical Data Sheet

AF-884

Ingredient	Silicone oil and hydrophobic particles of water
	emulsion
Warranty	6 months (kept in a cool, dry place at room
	temperature)
Applications	AF-884 is used in
	 Black liquor for paper and pulping
	Wastewater treatment
Features	Resistant to strong alkali and high
	temperature
	Outstanding bubble inhibition ability

Physical indicators

Exterior White or yellowish milky liquid

Solid content (39-41) %

pH value 6.5-9.0

Viscosity, **25**°C 2000-8000mPa.s

Instructions • It can be used directly or diluted to a low content.



- Can be diluted directly with water, but need to be used immediately, if the dilution needs to be stored for a certain time, you can consult our company, our company will provide professional dilution method.
- The recommended addition amount of pulping black liquor is 0.05~0.5kg per ton of pulp, and the addition amount of sewage treatment is generally 10~1000ppm, and the optimal addition amount is determined according to the actual situation on site.
- The addition point is generally selected where the defoamer is easily dispersed, and can be continuously added with a metering pump.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away
 from direct sunlight



Data
as
se
1,
L

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.