

Technical Data Sheet

AF-900

Ingredient Silicone oils, hydrophobic particles and synergists

Warranty 6 months (kept in a cool, dry place at room temperature)

Applications AF-900 is used in

- Industrial water treatment
- Textile additives
- Water-based ink

Features ● The bubble inhibition ability is outstanding

- Good acid and alkaline resistance
- Good compatibility with the system

Physical indicators

Exterior White or yellowish milky liquid

Viscosity, 25°C 500~2000mPa.s

Instructions ● Directly added use, can also be diluted to low content use.

- Can be diluted directly with water, but need to be used immediately, if the dilution needs to be stored for a certain time, you can

consult our company, our company will
provide professional dilution method.

- Add 100~1000ppm.
- The optimal addition amount depends on the actual situation on site.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away from direct sunlight
- Refer to the product' s Material Safety Data Sheet (MSDS) before use

Usage

- Not for human injection

restrictions

- This product is not tested or represented as suitable for medical or pharmaceutical use

Package

- 25kg/200kg plastic drum or 1000kg IBC drum
-

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.