

Technical Data Sheet

AF-910

Ingredient	Modified silicone oil, hydrophobic particles and
	synergists
Warranty	6 months (kept in a cool, dry place at room
	temperature)
Applications	AF-910 is used in
	Water-based ink
	• All kinds of latex paint
	 All kinds of water-based coatings
Features	Excellent compatibility
	 Suitable for a variety of resin systems
	• Excellent dynamic defoaming and defoaming
	ability

Physical indicators

Exterior Milky white viscous liquid

Solid content (50 ± 1) %

pH value 6.5-8.5

Viscosity, 25°C 2000~5000mPa.s

Instructions • Use it directly, or use it after pre-dispersing with materials.



- Add $0.2 \sim 0.5\%$ of the total formula.
- The optimal addition amount depends on the actual situation on site.
- It is recommended to add 50% before and after grinding.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away
 from direct sunlight
- Refer to the product's Material Safety Data
 Sheet (MSDS) before use

Usage

Not for human injection

restrictions

 This product is not tested or represented as suitable for medical or pharmaceutical use

Package

25kg/200kg plastic drum or 1000kg IBC drum

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.