

Technical Data Sheet

AF-916

Ingredient Silicone oil and hydrophobic particles of water emulsion

Warranty 6 months (kept in a cool, dry place at room temperature)

Applications AF-916 is used in

- Wood paint
- Gloss oil

Features ● Fast defoaming speed

- Good compatibility

Physical indicators

Exterior White or yellowish milky liquid

Solid content (24-26) %

pH value 6.5-8.5

Viscosity, 25°C 1000-5000mPa.s

Instructions ● It can be used directly, or can be pre-dispersed after use.

- The addition amount is generally 0.1~0.6%, and the optimal addition amount is adjusted

according to the actual situation on site.

- Precautions**
- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
 - Storage at room temperature (5-40°C), away from direct sunlight
 - Refer to the product's Material Safety Data Sheet (MSDS) before use
-

Usage ● Not for human injection

restrictions ● This product is not tested or represented as suitable for medical or pharmaceutical use

Package ● 25kg/200kg plastic drum or 1000kg IBC drum

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.