

Technical Data Sheet

AF-890

Ingredient	Silicone oils, hydrophobic particles and
	synergists
Warranty	6 months (kept in a cool, dry place at room
	temperature)
Applications	AF-890 is used in
	• Steel plate cleaning
	• Power plant trip
Features	 Outstanding bubble inhibition ability
	 Good acid and alkaline resistance
	• Good compatibility with the system
Physical indicators	
Exterior	Colorless to pale yellow cloudy liquid
Viscosity, 25°C	C 300~1500mPa.s
Instructions	Directly add and use, not recommended after
	diluting with water.
	• Add 100~1000ppm.
	• The optimal addition amount depends on the
	actual situation on site.



• The addition point is generally the part where the foam is rich and the defoamer is easy to disperse.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away
 from direct sunlight
- Refer to the product's Material Safety Data
 Sheet (MSDS) before use

Usage

Not for human injection

restrictions

 This product is not tested or represented as suitable for medical or pharmaceutical use

Package

 25kg/200kg plastic drum or 1000kg IBC drum

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.