

Technical Data Sheet

AF-910

Ingredient	Modified silicone oil, hydrophobic particles and
	synergists
Warranty	6 months (kept in a cool, dry place at room
	temperature)
Applications	AF-910 is used in
	• Water-based ink
	• All kinds of latex paint
	• All kinds of water-based coatings
Features	• Excellent compatibility
	• Suitable for a variety of resin systems
	• Excellent dynamic defoaming and defoaming
	ability
Physical indicators	
Exterior	Milky white viscous liquid
Solid conte	nt (50 ± 1) %

pH value 6.5-8.5

Viscosity, 25°C 2000~5000mPa.s



- Instructions Use it directly, or use it after pre-dispersing with materials.
 - Add $0.2 \sim 0.5\%$ of the total formula.
 - The optimal addition amount depends on the actual situation on site.
 - It is recommended to add 50% before and after grinding.
- Precautions
 There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
 - Storage at room temperature (5-40°C), away from direct sunlight
 - Refer to the product's Material Safety Data Sheet (MSDS) before use
- Usage Not for human injection
 restrictions This product is not tested or represented as suitable for medical or pharmaceutical use
 Package 25kg/200kg plastic drum or 1000kg IBC drum



Add:No. 78 Bancang Street,Xuanwu District, Nanjing City, Jiangsu Province, China Tel:+86 13062866000 Web:www.antifoamchemical.com

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.