

Technical Data Sheet

AF-722

Ingredient	Mineral oil and hydrophobic particles
Warranty	6 months (kept in a cool, dry place at room
	temperature)
Applications	AF-722 is used in
	• Pure acrylic emulsion, vinegar acrylic latex
	paint
	 Water-based adhesive
	 Water-based ink and high-grade interior wall
	latex paint
Features	 It is especially effective for breaking
	microbubbles
	 Good compatibility, no surface defects
	No adverse effect on luster

Physical indicators

Exterior Beige opaque cloudy liquid

Solid content 100%

pH value 5.0-8.0

Viscosity, 25°C 500-5000mPa.s



Instructions

- It is best to stir thoroughly before use, even if the surface is not layered; Long-term storage may be slightly stratified, stir evenly after use, does not affect the effect.
- Can be directly added to use, can also be pre-dispersed after use.
- The addition amount is generally 0.1~0.6%, and the optimal addition amount is adjusted according to the actual situation on site.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away
 from direct sunlight
- Refer to the product's Material Safety DataSheet (MSDS) before use

Usage

• Not for human injection

restrictions

 This product is not tested or represented as suitable for medical or pharmaceutical use

Package

 25kg/50kg/180kg plastic drum or 850kg IBC drum





LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.